



Exposure units for the production of screen printing stencils

Overview without prices 2020





Retouching Stand, 110x140

Model: 11007110140

for max. screen size: 110x140cm, 230V, 50Hz

Made of synthetic material, with steel-tube stand, incl. adjustable aluminium positioning rails.



Retouching Stand, 140x180

Model: 11007140180

for max. screen size: 140x180cm, floor space: approx. 150x 55cm, 230V, 50Hz

Made of synthetic material, with steel-tube stand, incl. adjustable aluminium positioning rails.



Retouching and Coating Stand, 110x140

Model: 11008110140

for max. screen size: 110x140cm, 230V, 50Hz

With illuminated back panel, white and yellow light, top and bottom clamp rail, height-adjustable, made of synthetic material, with steel-tube stand.



Retouching and Coating Stand, 140x180

Model: 11008140180

for max. screen size: 140x180cm, 230V, 50Hz

With illuminated back panel, white and yellow light, top and bottom clamp rail, height-adjustable, made of synthetic material, with steel-tube stand.



Developing and Decoating Basin PP-STAR Model 1, 110x140
Model: 12001110140
for max. screen size: 110x140cm, 230V, 50Hz, 0.4kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 2, 120x140
Model: 12001120140
for max. screen size: 120x140cm, 230V, 50Hz, 0.4kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 3, 140x180
Model: 12001140180
for max. screen size: 140x180cm, 230V, 50Hz, 0.4kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 4, 150x220
Model: 12001150220
for max. screen size: 150x220cm, 230V, 50Hz, 1.0kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 5, 160x260
Model: 12001160260
for max. screen size: 160x260cm, 230V, 50Hz, 1.0kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 6, 160x300
Model: 12001160300
for max. screen size: 160x300cm, 230V, 50Hz, 1.0kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 7, 180x350
Model: 12001180350
for max. screen size: 180x350cm, 230V, 50Hz, 1.0kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Developing and Decoating Basin PP-STAR, Model 8, 200x400
Model: 12001200400
for max. screen size: 200x400cm, 230V, 50Hz, 1.0kW
Completeley made of polypropylene (resistant against chemicals and solvents), with illumination from the back, support with storage board, side parts, and doors, incl. holder for high-pressure pistol and developing brush.



Cascade filter tank, model 1 approx. 280 l tank
Model: 12002009
with coarse filter and 3 overflows, pull-out cascade for complete emptying.



Cascade filter tank, model 2 approx. 450 l tank
Model: 12002010
with coarse filter and 3 overflows, pull-out cascade for complete emptying.



Roll Frame for Cascade Filter Tank, model 1 (280L)
Model: 12002011
Frame made of angle profile, movable on 4casters. for easily roll in and out.



Roll Frame for Cascade Filter Tank, model 1 (450L)
Model: 12002012
Frame made of angle profile, movable on 4casters. for easily roll in and out.



Developing and Decoating Basin SIMPLA, Model 1, 110x140
Model: 12002110140
Model 1: for max. frame size 110 x 140 cm, machine dimension BxTxH: approx. 135x76x200cm, underframe demountable/removable (height minus 50cm), 230V, 50Hz, 0,4kW made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin SIMPLA Model 2, 120x140
Model: 12002120140
Model 2: for max. frame size 120 x 140 cm, machine dimension BxTxH: approx. 145x76x200cm, underframe demountable/removable (height minus 50cm), 230V, 50Hz, 0,4kW made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin SIMPLA, Model 3, 140x180
Model: 12002140180
Model 3: for max. frame size 140x180cm, machine dimension BxTxH: approx. 200x76x200cm, underframe demountable/removable (height minus 50cm), floor space: approx. 210x 90cm, 230V, 50Hz, 0,4kW made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin SIMPLA, Model 4, 150x220
Model: 12002150220
Model 4: for max. frame size 150x220cm, machine dimension BxTxH: appr. 250x76x210cm, underframe demountable/removable (height minus 50cm), 230V, 50Hz, 1.0kW made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin SIMPLA, Model 5

Model: 12002160260

model 5: for max. frame size 160 x 260 cm, machine dimension BxTxH: appr. 300x76x220cm, underframe demountable/removable (height minus 50cm)

made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin SIMPLA, Model 6, 160x300

Model: 12002160300

Model 6: for max. frame size 160x300cm, machine dimension BxTxH: approx. 350x76x220cm, underframe demountable/removable (height minus 50cm), 230V, 50Hz, 1.0kW

made of polypropylen, with open steel-tube support, incl. hand spray with hose.



Developing and Decoating Basin SIMPLA, Model 7, 180x350

Model: 12002180350

Model 7: for max. frame size 180x350cm, machine dimension BxTxH: approx. 400x76x240cm, underframe demountable/removable (height minus 50cm), 230V, 50Hz, 1.0kW

made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin SIMPLA, Model 8, 200x400

Model: 12002200400

Model 8: for max. frame size 200 x 400 cm, machine dimension BxTxH: approx. 450x76x260cm, underframe demountable/removable (height minus 50cm), 230V, 50Hz, 1.0kW

made of polypropylen, with open steel-tube support, incl. hand shower with hose.



Developing and Decoating Basin LABOR, Model 1

Model: 12003064078

For max. screen size: 60x80cm, outer dimension W/D/H: 80x78x200cm, 230V, 50Hz, 0.2kW

Completely made of polypropylene, with illumination from the back, vertical insertion of screen frames, incl. hand shower with hose.



Developing and Decoating Basin LABOR, Model 2

Model: 12003104086

For max. screen size: 100x 80cm, outer dimension: 120x78x200cm, 230V, 50Hz, 0.2kW

Completely made of polypropylene, with illumination from the back, vertical insertion of screen frames, incl. hand shower with hose.



Developing and Decoating Basin LABOR, Model 3

Model: 12003134086

For max. screen size: 130x100cm, outer dimension W/D/H: 150x78x200cm, 230V, 50Hz, 0.2kW

Completely made of polypropylene, with illumination from the back, vertical insertion of screen frames, incl. hand shower with hose.



Water Vacuum Cleaner Model WAP

Model: 09002100

with 25 cm wide nozzle, made of synthetic material, 230V, 50Hz



Valve Hand Shower from Stainless Steel, Connection: 1/2inch

Model: 40100012



Rubber Hose, black, 3m / 1/2inch

Model: 40100003



Aluminium Washing Brush with Shutter and Brush

Model: 40100009

for manual screen washing units/squeegee washing unit



Brush for Aluminum Shutter

Model: 40100010

Spare Part for Hand Washing Brush



Rubber Hose, black, 1.5m / 1/2inch

Model: 40100015



Rubber Hose, black, 6m, 1/2inch

Model: 40100033



Development Sprinkler with Quick Connection

Model: 40100100

Water jet adjustable. Please observe: a quick coupling is necessary!



Quick Coupling for Development Sprinkler

Model: 40100101

with connection for water hose 1/2"



Hose for Water Vacuum Cleaner model WAP, length: 3m

Model: 40115003

with dutch



High pressure emulsion remover model KRÄNZLE

Model: 09001KR60

working pressure, infinitely adjustable: 30-80bar, connections: 230V, 7.5A, 50Hz

With adjustable unloader-valve, high-pressure pistol with adjustable nozzle. Device suitable for temporary operation, 230V.



Coating Stand for floor mounting

Model: 090181001

for screen frames up to max. 140x180cm

Simple stand for fixing the screen stencils for direct coating. Plastic coated steel tube construction.



Coating Stand for wall mounting

Model: 090181002

for screen frames up to max. 140x180cm

Simple stand for fixing the screen stencils for direct coating. Plastic coated steel tube construction.



Combined Exposure Unit, Model 1, 75x95, 1.5kW
Model: 01004075095
Max. screen size: 75x95cm, MH quick-start lamp: 1.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 2, 95x120, 3.5kW
Model: 01004095120
Max. screen size: 95x120cm, MH-quick-start lamp: 3.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 3, 110x135, 3.5kW
Model: 01004110135
Max. screen size: 110x135cm, MH quick-start lamp: 3.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 3, 110x135, 5.5kW
Model: 010041101351
Max. screen size: 110x135cm, MH quick-start lamp: 5.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 4, 120x145, 3.5kW
Model: 01004120145
Max. screen size: 120x145cm, floor space: approx. 250x 190cm, MH quick-start lamp: 3.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 4, 120x145, 5.5kW
Model: 010041201451
Max. screen size: 120x145cm, MH quick-start lamp: 5.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 5, 130x160, 3.5kW
Model: 01004130160
Max. screen size: 130x160cm, MH quick-start lamp: 3.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 5, 130x160, 5.5kW
Model: 010041301601
Max. screen size: 130x160cm, MH quick-start lamp: 5.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Modell 6, 140x180, 3.5kW
Model: 01004140180
Max. screen size: 140x180cm, MH quick-start lamp: 3.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 6, 140x180, 5.5kW
Model: 010041401801
Max. screen size: 140x180cm, MH quick-start lamp: 5.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 7, 150x220, 3.5kW
Model: 01004150220
Max. screen size: 150x220cm, MH quick-start lamp: 3.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Combined Exposure Unit, Model 7, 150x220, 5.5kW
Model: 010041502201
Max. screen size: 150x220cm, MH quick-start lamp: 5.5kW, connection: 400V/50cycles, CEE-plug, 32ampere.
consisting of steel-tube support with storage board, with 4retractable drawers, with pull-out rails for various sizes of screens, vacuum copying frame with flexible rubber blanket on top, easier lifting of the glass upper frame by gas springs, height-adjustable cross-beam on top with hanging MH exposure lamp model AKTICOP S as well as UV-protection curtain, with light dosing device model AKTITRON S16E, 16programs, equipped with light sensor at the copying frame. Control board at the drying cabinet with vacuum gauge, vacuum reducing valve, operating and control elements.



Screen Exposure Unit VARIOCOP S, 1.5kW, Model 67x77cm
Model: 010050670771
Screen frame size: approx. 47x57cm, internal glass plate size: approx. 67x77cm, metal-halide quick start lamp: 1500W, connection: 230V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames, suitable for all applications of screen printing, with sturdy all-steel housing, with light dosing device AKTITRON S16E incl. photo cell, with 16programs.



Screen Exposure Unit VARIOCOP S, 3,5kW, Model 67x77cm
Model: 010050670773
Screen frame size: approx. 47x57cm, internal glass plate size: 67x77cm, metal-halide quick start lamp: 3500W, 400V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames for all kinds of use of screen printing, with sturdy all-steel housing, light dosing device AKTITRON S16E incl. photo cell, with 16programs.



Screen Exposure Unit VARIOCOP S, 3,5kW, Model: 72x92cm
Model: 010050720923
Screen frame size: approx. 53x73cm, internal glass plate size: approx. 72x92cm, metal-halide quickstart lamp: 3500W, 400V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames for all kinds of use of screen printing, with sturdy all-steel housing, light dosing device AKTITRON S16E incl. photo cell, with 16programs.



Screen Exposure Unit VARIOCOP S, 3,5kW, Model 82x102cm
Model: 010050821023
Screen frame size: approx. 62x82cm (internal glass plate size: approx. 82x102cm), metal-halide quick start lamp: 3500W, 400V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames for all kinds of use of screen printing, with sturdy all-steel housing, light dosing device AKTITRON S16E incl. photo cell, with 16programs.



Screen Exposure Unit VARIOCOP S, 3,5kW, Model 92x112cm
Model: 010050921123
Screen frame size: approx. 73x93cm (internal glass plate size: approx. 92x112cm), metal halide quick start lamp: 3500W, 400V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames for all kinds of use of screen printing, with sturdy all-steel housing, light dosing device AKTITRON S16E incl. photo cell, with 16programs.

Exposure Units > Combined Exposure > New



Screen Exposure Unit VARIOCOP S, 3,5kW, Model 110x130cm
Model: 010051101303
Screen frame size: approx. 90x110cm (internal glass plate size: 110x130cm), metal-halide quick start lamp: 3500W, 400V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames for all kinds of use of screen printing, with sturdy all-steel housing, light dosing device AKTITRON S16E incl. photo cell, with 16programs.



Screen Exposure Unit VARIOCOP S, 5,5kW, Model 120x145cm
Model: 010051201455
Screen frame size: approx. 100x125cm (internal glass plate size: approx. 120x145cm), metal-halide quick start lamp: 5500W, 400V, 50Hz
Professional unit for exposure of UV-sensible emulsions and films on small till big sizes screen frames for all kinds of use of screen printing, with sturdy all-steel housing, light dosing device AKTITRON S16E incl. photo cell, with 16programs.



Screen Exposure Unit VARIOCOP S COMBI, 1,5kW, Model 67x77cm
Model: 010130670771
Screen frame size: approx. 47x57cm, internal glass plate size: approx. 67x77cm, incl. drying cabinet with 3drying drawers, light dosing device AKTITRON S16E, metal-halide quickstart lamp: 1500W, 230V, 50Hz
Professional copying unit with 3thermostatically adjustable drying drawers, each with 4angled screen supports, for the exposure and drying of UV-sensitive emulsions and films on small up to medium sized screen frames, with sturdy steel housing and light dosing device AKTITRON S16E with photo cell, 16programmes.



Screen Exposure Unit VARIOCOP S COMBI, 3,5kW, Model 67x77cm
Model: 010130670773
Screen frame size: approx. 47x57cm, internal glass plate size: approx. 67x77cm, incl. drying cabinet with 3drying drawers, light dosing device AKTITRON S16E, metal-halide quickstart lamp: 3500W, 400V, 50Hz
Professional copying unit with 3thermostatically adjustable drying drawers, each with 4angled screen supports, for the exposure and drying of UV-sensitive emulsions and films on small up to medium sized screen frames, with sturdy steel housing and light dosing device AKTITRON S16E with photo cell, 16programmes.

Exposure Units > Combined Exposure > New



Screen Exposure Unit VARIOCOP S COMBI, 1,5kW, Model 72x92cm
Model: 010130720921
Screen frame size: approx. 53x73cm, internal glass plate size: approx. 72x92cm, incl. drying cabinet with 3drying drawers, light dosing device AKTITRON S16E, metal-halide quickstart lamp: 1500W, 230V, 50Hz
Professional copying unit with 3thermostatically adjustable drying drawers, each with 4angled screen supports, for the exposure and drying of UV-sensitive emulsions and films on small up to medium sized screen frames, with sturdy steel housing and light dosing device AKTITRON S16E with photo cell, 16programmes.



Screen Exposure Unit VARIOCOP S COMBI, 3,5kW, Model 72x92cm
Model: 010130720923
Screen frame size: approx. 53x73cm, internal glass plate size: approx. 72x92cm, incl. drying cabinet with 3drying drawers, light dosing device AKTITRON S16E, metal halide quickstart lamp: 3500W, 400V, 50Hz
Professional copying unit with 3thermostatically adjustable drying racks, each with 4angled screen supports, for the exposure and drying of UV-sensitive emulsions and films on small till medium sized screen frames, with sturdy steel housing and light dosing unit AKTITRON S16E with photo cell, 16programmes.



Screen Exposure Unit VARIOCOP S COMBI, 3,5kW, Model 82x102cm
Model: 010130821023
Screen frame size: approx. 62x82cm, internal glass plate size: approx. 82x102cm, incl. drying cabinet with 3drying drawers, light dosing device AKTITRON S16E, metal-halide quickstart lamp: 3500W, 400V, 50Hz
Professional copying unit with 3thermostatically adjustable drying racks, each with 4angled screen supports, for the exposure and drying of UV-sensitive emulsions and films on small till medium sized screen frames, with sturdy steel housing and light dosing unit AKTITRON S16E with photo cell, 16programmes.



Screen Exposure Unit VARIOCOP S COMBI, 3,5kW, Model 92x112cm
Model: 010130921123
Screen frame size: approx. 73x93cm, internal glass plate size: approx. 92x112cm, incl. drying cabinet with 3drying drawers, light dosing device AKTITRON S16E, metal-halide quickstart lamp: 3500W, 400V, 50Hz
Professional copying unit with 3thermostatically adjustable drying racks, each with 4angled screen supports, for the exposure and drying of UV-sensitive emulsions and films on small till medium sized screen frames, with sturdy steel housing and light dosing unit AKTITRON S16E with photo cell, 16programmes.



Light Dosing Device, S16A Aktitron, 16 programs

Model: 01103016

with housing and photo cell, connection cable: approx. 2m, cable photo cell: approx. 5m (standard length, upon request longer available)



Vacuum Exposure Unit, Table-top Model 1, 40x50
Model: 01001040050
Model 1: for max. screen size 40x50cm, vacuum pump 4cbm, connection: 230V, 50Hz
With high flexible rubber blanket, strong 4cbm vacuum pump 230 volts, suitable for horizontal exposure of smaller screen frames.



Vacuum Exposure Unit, Table-top Model 2, 50x60
Model: 01001050060
Model 2: for max. screen size 50 x 60 cm, vacuum pump 4cbm, connection: 230V, 50Hz
With high flexible rubber blanket, strong 4cbm-vacuum pump 230volts, suitable for horizontal exposure of smaller screen frames.



Vacuum Exposure Unit, Table-top Model 3, 60x80
Model: 01001060080
Model 3: for max. screen size 60x80cm, vacuum pump 4cbm, connection: 230V, 50Hz
With high flexible rubber blanket, strong 4cbm-vacuum pump 230volts, suitable for horizontal exposure of smaller screen frames.



Vacuum Exposure Unit, Table-top Model 4, 80x100
Model: 01001080100
model 4 - for max. screen size 80x100cm, with 4cbm vacuum pump, connection: 230V, 50Hz
With high flexible rubber blanket, strong 4cbm vacuum pump 230 volts, suitable for horizontal exposure of smaller screen frames.



Vacuum Exposure Unit, Swivelling Floor Model, I: 105x135
Model: 01002105135
Model I: for max. screen size: 105x135cm, with vacuum pump: 4cbm, connection: 230V, 50Hz
with yellow built-in light source, highly flexible rubber blanket, strong vacuum pump, with swivelling frame therefore suitable for horizontal and vertical exposure, upper frame easy to open by gas springs.



Vacuum Exposure Unit, Swivelling Floor Model, II: 135x165

Model: 01002135165

Model II: for max. screen size: 135x165cm, with vacuum pump: 4cbm, connection: 230V, 50Hz with yellow built-in light source, highly flexible rubber blanket, strong vacuum pump, with swivelling frame therefore suitable for horizontal and vertical exposure, upper frame easy to open by gas springs.



Vacuum Exposure Unit, Swivelling Floor Model, III: 155x195

Model: 01002155195

Model 3: for max. screen size: 155x195cm, with vacuum pump: 4cbm, connection: 230V, 50Hz with yellow built-in light source, highly flexible rubber blanket, strong vacuum pump, with swivelling frame therefore suitable for horizontal and vertical exposure, upper frame easy to open by gas springs.



UV Tube Exposure Unit, 60x80
Model: 01007060080
Table-top model with 6 actinic UV tubes, each 40watts, for max. screen size: 60x80cm, total height: 40cm, connection: 230V, 50Hz
Table-top model, suitable for simple lines and rough halftone copies, with carburize rubber blanket, with yellow built-in light source, powerful vacuum pump, exposure timer, manual/automatic switch.



UV Tube Exposure Unit, 80x120
Model: 01007080120
Table-top model with 6 actinic UV tubes, each 40watts, for max. screen size: 80x120cm, total height: 40cm, connection: 230V, 50Hz
Table-top model, suitable for simple lines and rough halftone copies, with carburize rubber blanket, with yellow built-in light source, powerful vacuum pump, exposure timer, manual/automatic switch.



UV Tube Exposure Unit, 100x120
Model: 01007100120
Table-top model with 8 actinic UV tubes, each 40watts, for max. screen size: 100x120cm, total height: 40cm, connection: 230V, 50Hz
Table-top model, suitable for simple lines and rough halftone copies, with carburize rubber blanket, with yellow built-in light source, powerful vacuum pump, exposure timer, manual/automatic switch.



UV Tube Exposure Unit, 120x160
Model: 01007120160
Table-top model with 13 actinic UV tubes, each 40watts, for max. screen size: 120x160cm, total height: 40cm, connection: 230V, 50Hz
Table-top model, suitable for simple lines and rough halftone copies, with carburize rubber blanket, with yellow built-in light source, powerful vacuum pump, exposure timer, manual/automatic switch.



UV Tube Exposure Unit, 140x180
Model: 01007140180
Table-top model with 17 actinic UV tubes, each 40watts, for max. screen size: 140x180cm, total height: 40cm, connection: 230V, 50Hz
Table-top model, suitable for simple lines and rough halftone copies, with carburize rubber blanket, with yellow built-in light source, powerful vacuum pump, exposure timer, manual/automatic switch.



Additional price for steel-tube support model 1 (58x78 cm)
Model: 01012001
with storage board



Additional price for steel-tube support model 2 (78x100)
Model: 01012002
with storage board



Metal-Halide Exposure Lamp AKTICOP-S 1500 S, horizontal
Model: 011031500
1500watts, 230V, 50Hz, horizontal with hanging attachment
metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector. Hanging lamp



Metal-Halide Exposure Lamp AKTICOP-S 1500 S, vertical
Model: 011031500S
1500watts, 230V, 50Hz, vertical with mobile stand
metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector. Lamp with stand



Metal-Halide Exposure Lamp AKTICOP-S 3500 S, horizontal
Model: 011033500
3500watts, 400V, 50Hz, horizontal with hanging attachment
metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector.



Metal-halide Exposure Lamp AKTICOP-S 3500 S, vertical
Model: 011033500S
3500watts, 400V, 50Hz, vertical with mobile stand
metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector. Lamp with stand



Metal-Halide Exposure Lamp AKTICOP-S 5500 S, horizontal
Model: 011035500
5500watts, 400V, 50Hz, horizontal with hanging attachment
metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector.



Metal-Halide Exposure Lamp AKTICOP-S 5500 S, vertical

Model: 011035500S

5500watts, 400V, 50Hz, vertical with mobile stand

metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector.



Metal-halide exposure lamp AKTICOP-S 7500 S + S16E

Model: 011037500

7500watts, 400V, 50Hz, incl. light dosing device AKTITRON S16E with 16 programs, horizontal with hanging attachment

metal-halide exposure lamp for the precise exposure of stencils. New type of high gloss reflector. Hanging lamp



Metal-Halide Exposure Lamp AKTICOP-S 7500 S + S16E

Model: 011037500S

7500watts, 400V, 50Hz, incl. light dosing device AKTITRON S16E with 16 programs, vertical completely with mobile stand

metal-halide quick-start exposure lamp for the precise exposure of stencils. New type of high gloss reflector.

Exposure Units > Exposure lamps > Accessories



Exposure timer S1A, digital
Model: 01103005



UV-Tube, 1000mm, ø 19mm, Hg-doped, ozone-forming
Model: 400011000-19
for AKTIPRINT UV-Dryer, 10 kW



UV-Tube, 1000mm, ø 19mm, Ga-doped, ozone-forming
Model: 400011000-19Ga
for AKTIPRINT UV-Dryer



UV-Tube, 1000mm, ø 22,5mm, Fe-doped, ozone-forming
Model: 400011000-22Fe
for AKTIPRINT UV-Dryer



1.2kW MH-Tube, 1200watt, Ga doped
Model: 400031200
for Metal halide lamp



MH tube 1500 watts
Model: 400031500
for metal halid quickstart exposure lamp Akticop 1500 S



3kW MH-Tube, 3000Watt, Ga
Model: 400033000
Metal halide lamp



3kW MH-Tube, 3200Watt (short)
Model: 400033200-01
MH-tube for contacting device



MH-tube S 3500 watts
Model: 400033500
quickstart metal halide bulb
Schnellstart-Metallhalogenidstrahler



5kW MH-tube, 5000watts, Ga
Model: 400035000
Metal halide lamp



MH-Tube S 5500watts
Model: 400035500
for MH quickstart exposure lamp Akticop 5500 S



MH tube S 7500watts, hg, ozone-forming
Model: 400037500Hg
for MH quickstart exposure lamp Akticop 7500 S



AMBA MH-Tube 3500watts for UNI-BOX
Model: 400043500AM



Flourescent Lamp, yellow, 18W, 600mm
Model: 4000618060G
Yellow light tube for exposure unit



Flourescent Tube, yellow, 36W, 1200mm
Model: 4000636120G



Flourescent Lamp, yellow, 58W, 1500mm
Model: 4000658150G



Calmat Tube SBL2, 1000watt

Model: 400SBL002

Tube with high UV-light emission



Calmat Tube SBL4, 2000watt

Model: 400SBL004

Tube with high UV-light emission



Spare Bulb SOL 300, socket E27, 300W

Model: 400SOL300-OS

for exposure lamp 230V. Attention: This lamp was especially measured for specific UV-radiation. Do not use for irradiation of people.



Pneumatic Spring for Copying Frame, 300/400/500 Newton

Model: 401200-400



Dark Room Bulb, yellow

Model: 59345331

220 W, E 27, 4533



Dark Room Bulb, green

Model: 59345341

220 W, E 27, 4533



Dark Room Bulb, red

Model: 59345631

220 W, E 27, 4533

Exposure Units > Screen drying cabinet > New



Screen Drying Cabinet SUPER THERM, Model 1: 80x100
Model: 04001080100
For max. screen size: 80x100cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPER THERM, Model 2: 95x120
Model: 04001095120
For max. screen size: 95x120cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPER THERM, Model 3: 110x135
Model: 04001110135
For max. screen size: 110x135cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPER THERM, Model 4: 120x145
Model: 04001120145
For max. screen size: 120x145cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPER THERM, Model 5: 125x160
Model: 04001125160
For max. screen size: 125x160cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.

Exposure Units > Screen drying cabinet > New



Screen Drying Cabinet SUPERTHERM, Model 6: 140x180
Model: 04001140180
For max. screen size: 140x180cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPERTHERM, Model 7: 140x200
Model: 04001140200
For max. screen size: 140x200cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPERTHERM, Model 8: 150x220
Model: 04001150220
For max. screen size: 150x220cm, connection: 400V,50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPERTHERM, Model 9: 160x260
Model: 04001160260
For max. screen size: 160x260cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.



Screen Drying Cabinet SUPERTHERM, Model 10: 180x300
Model: 04001180300
For max. screen size: 180x300cm, connection: 400V, 50Hz, 6kW
Sturdy drying cabinet in full steel construction, with 5 drawers smoothly moving on ball bearings. Good air circulation, with thermostat and timer, with white plastic-coated plate on top, can be used as deposit place.

Exposure Units > Screen drying cabinet > New



Screen Drying Cabinet SUPERTHERM VTK, Model 1: 80x100
Model: 04003080100
for max. screen size: 80x100cm, outer dimension: approx. 85cm wide (+control box) x 90cm deep x 140cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8 screen guide rails, 2swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 2: 95x120
Model: 04003095120
for max. screen size: 95x120cm, outer dimension: approx. 85cm wide (+ control box) x 105cm deep x 160cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8screen guide rails, 2swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 3: 110x135
Model: 04003110135
for max. screen size: 110x135cm, outer dimension: approx. 85cm wide (+ control box) x 120cm deep x 175cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8 screen guide rails, 2 swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 4: 120x145
Model: 04003120145
for max. screen size: 120x145cm, outside dimension: approx. 85cm wide (+ control box) x 130cm deep x 185cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8 screen guide rails, 2 swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.

Exposure Units > Screen drying cabinet > New



Screen Drying Cabinet SUPERTHERM VTK, Model 5: 125x160
Model: 04003125160
for max. screen size: 125x160cm, outside dimension: approx. 85cm wide (+ control box) x 135cm deep x 200cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8screen guide rails, 2swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 6: 140x180
Model: 04003140180
for max. screen size: 140x180cm, outer dimension: approx. 85cm wide (+ control box) x 190cm deep x 180cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8 screen guide rails, 2 swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 7: 140x200
Model: 04003140200
for max. screen size: 140x200cm, outer dimension: approx. 85cm wide (+ control box) x 210cm deep x 180cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8screen guide rails, 2swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 8: 150x220
Model: 04003150220
for max. screen size: 150x220cm, outer dimension: approx. 85cm wide (+ control box) x 230cm deep x 190cm high, connection: 400V, 50Hz, 6kW
All-steel construction, vertical version with 8screen guide rails, 2swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 9: 160x260

Model: 04003160260

for max. screen size: 160x260cm, outer dimension: approx. 85cm wide (+ control box) x 270cm deep x 200cm high, connection: 400V, 50Hz, 6kW

All-steel construction, vertical version with 8screen guide rails, 2swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.



Screen Drying Cabinet SUPERTHERM VTK, Model 10: 180x300

Model: 04003180300

for max. screen size: 180x300cm, outer dimension: approx. 85cm wide (+ control box) x 310cm deep x 220cm high, connection: 400V, 50Hz, 6kW

All-steel construction, vertical version with 8 screen guide rails, 2 swivelling doors with vertical locking, good air circulation, with thermostat and timer for manual or automatic use. For an upright setting of screen frames.