
Technical Information





Update: 21.01.13

KIWODUR[®] 933 RAPID

Hardener for the two-component screen adhesive KIWOBOND 933 RAPID

KIWODUR 933 RAPID is a dyed hardener for KIWOBOND 933 RAPID giving the adhesive mixture a strong orange-red colour. A visual control of the applied adhesive quantity is therefore possible. For details about application and properties please refer to the technical data sheet for the adhesive component.

BASIS	Polyisocyanate, containing solvents
COLOUR	Red, transparent
SOLIDS CONTENT	Approx. 32%
DENSITY	Approx. 1,02 g/cm ³
FLASH POINT	Approx4°C
HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION	Please follow further information given in the material safety data sheet.
STORAGE	2 years (at 20 – 25°C in original container)
	KIWODUR 933 RAPID is sensitive to humidity and must therefore be stored

KIWODUR 933 RAPID is sensitive to humidity and must therefore be stored in the tightly closed original container. Avoid storage at higher temperatures.

This data sheet is for your information, a legally binding guarantee of the product's suitability for a particular application cannot be derived. No responsibility can be undertaken for occurring damages. Our products are subject to a continuous production and quality control and leave our factory in perfect condition.