

# Reinigungsautomat Typ K 40 / 60 / 80



Reinigungsautomat aus Edelstahl zur Kaltreinigung mit Lösemitteln in den Bereichen Siebdruck, Tampondruck und Klischeereinigung, inkl. Niveauekontrolle, Deckelverriegelung und Partikelfilter mit Badabdeckblech. Geeignet für den Einsatz von Kaltreiniger der Gefahrenklasse A III (Flammpunkt über 55°C).  
Optional: Absaugstutzen an der hinteren Behälterwand.

Modell:	K 40	K 60	K 80
Korbdurchmesser Ø (mm):	400	580	800
Nutzbare Innenhöhe (mm):	260	370	530
Füllmenge (l):	20	50	100
Pumpleistung (l/min):	45	55	70
Korbbelastung (kg):	70	100	150
Gewicht (kg) ca.:	60	90	170
Außenmaß (B x T x H) (mm) ca.:	750 x 600 x 850	950 x 850 x 970	1350 x 1100 x 1270
Anschlussspannung:	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz

# Automatic Cleaning Device

## Type K 40/ 60/ 80



Cleaning device made of stainless steel for cold cleaning with solvents in the sectors of screen printing, pad printing and cliché cleaning, incl. lever control, cover locking mechanism, particle filter with solvent cover. Suitable for the use of solvents with flash point over 55°C (A III).  
Option: Exhaust connection at the container wall

Model:	K 40	K 60	K 80
Basket diameter Ø (mm):	400	580	800
Usable inner height (mm):	260	370	530
Filling capacity (l):	20	50	100
Pump capacity (l/min):	45	55	70
Basket loading from (kg):	70	100	150
Weight from (kg) ca.:	60	90	170
Outer measures (Bx Tx H) (mm) ca.:	750x 600x 850	950x 850x 970	1350x 1100x 1270
Power supply:	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz